

DLD2133-PNW V1 MaxRGB

21.3" TFT LCD, LED Backlight 600nits, MaxRGB UXGA (1600x1200)

The DLD2133-PNW is a 21.3 inch industrial grade sunlight readable and HCS (High Color Saturation) LCD, with high brightness 600 nits and high color saturation, it produce sharp images, crisp text and lifelike colors. The Durapixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor application, kiosk, factory automation, military, transportation and gaming application.



KEY FEATURES

- High Brightness 600 nits
- Sunlight Readable
- LED Backlight
- Low Power Consumption
- High Color Saturation
- BL MTBF: 100,000 hours

SPECIFICATIONS

Model No.	DLD2133-PNW V1
Description	21.3" TFT LCD, LED Backlight 600 nits,MaxRGB UXGA (1600x1200)
Display Area (mm)	432.0 (H) x 324.0(V)
Brightness	600 cd/m ²
Resolution	1600x1200
Aspect Ratio	4 : 3
Contrast Ratio	1500 : 1
Pixel Pitch (mm)	0.270(H) x 0.270(V)
Pixel Per Inch (PPI)	93
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	96%
Display Colors	16.7M
Response Time (Typical)	20ms
Panel Interface	LVDS
AD Board Input Interface	VGA, DVI, HDMI, DP, RS232
Input Power	DC12V
Power Consumption	33W
Dimensions (mm)	461.5 x 355.1 x 65.4
Bezel Size(U/B/L/R)	15.3/13.8/13.8/13.8 mm
Weight (Net)	6.5kg
Mounting	200x100, 100x100
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Operating Temperature	0 °C ~ 50 °C
Storage Temperature	-20 °C ~ 60 °C

*Specifications are subject to change without notice. **All brands or product names are trademarks or registered trademarks of their respective companies.

DLD/DLO = Panel+ LED Driving Board + Control Board + Housing

