

# DLF1333-H / DLH1333-H

13.3" Wide Temp TFT LCD, LED Backlight 600nits,XGA

13.3" TFT LCD panel, built-in 600 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marline, transportation, gaming, studio display, gas pump.



## KEY FEATURES

- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- Wide Operation Temperature. (-20°C ~ 70°C)
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy

## SPECIFICATIONS

Model No.	DLF1333-H / DLH1333-H
Description	13.3" TFT LCD, LED Backlight 600nits, XGA
Display Area (mm)	270.33 x 202.75mm
Brightness	600 cd/m <sup>2</sup>
Resolution	1024 x 768 (XGA)
Contrast Ratio	1200 : 1
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Viewing Angle	+80°~-80°(H), +70°~-80°(V)
Display Colors	262K
Response Time (Typical)	12ms
Sync	LVDS
Power Consumption	7W / 11.4W
Dimensions (mm)	284 x 215.5 x 6.8
Weight (Net)	440 g / 800g
LED Driving Board	LID 13A
Control Board (Optional)	<input type="checkbox"/> AD6038G <input type="checkbox"/> AD6038GA <input type="checkbox"/> AD6038GD <input type="checkbox"/> AD2662GDHVA
<input type="checkbox"/> AD6038G	VGA
<input type="checkbox"/> AD6038GA	VGA+Audio
<input type="checkbox"/> AD6038GD	VGA+DVI
<input type="checkbox"/> AD2662GDHVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component /HDMI)
F / R Control Button	<input type="checkbox"/> 4 Key <input type="checkbox"/> 5 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
<input type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

\*Specifications are subject to change without notice. \*\*All brands or product names are trademarks or registered trademarks of their respective companies.

DLF= Panel+LED Driving Board

DLH= Panel+LED Driving Board+Control Board

