

# SLD0868

8.4" TFT LCD Display, LED Backlight, 1600nits, SVGA(800x600)

8.4" TFT LCD panel, built-in 1600 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marline, transportation, gaming, studio display, gas pump.



## KEY FEATURES

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Wide Operation Temperature
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy

## SPECIFICATIONS

Model No.	SLD0868
Description	8.4" TFT LCD Display, LED Backlight, 1600nits, SVGA(800x600)
Display Area (mm)	170.4 x 127.8mm
Brightness	1600 cd/m <sup>2</sup>
Resolution	SVGA (800 x 600)
Contrast Ratio	600 : 1
Pixel Pitch (mm)	0.213 x 0.213
Viewing Angle	160°(H), 140°(V)
Display Colors	16.2M / 262K
Response Time (Typical)	35 ms
Power Consumption	9.7W
Dimensions (mm)	227 x 153.2 x 43.5mm
Weight (Net)	1.25Kg
LED Driving Board	LID08A06
Control Board (Optional)	<input type="checkbox"/> AD5621GA <input type="checkbox"/> AD5621GD <input type="checkbox"/> AD2662GDVAR
<input type="checkbox"/> AD5621GA	VGA+Audio
<input type="checkbox"/> AD5621GD	VGA+DVI
<input type="checkbox"/> AD2662GDVAR	VGA+DVI (Optional S□Video/ Component / Audio)
F / R Control Button	<input type="checkbox"/> 4 Key <input type="checkbox"/> 5 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
<input type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

\*Specifications are subject to change without notice. \*\*All brands or product names are trademarks or registered trademarks of their respective companies.

SLD/SLO = Panel+ LED Driving Board + Control Board + Housing

