

SLO1085

10.4" TFT LCD, LED Backlight 1000nits,XGA

10.4" TFT LCD panel, built-in 1000 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marline, transportation, gaming, studio display, gas pump.



KEY FEATURES

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- Wide Operation Temperature
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy

SPECIFICATIONS

Model No.	SLO1085
Description	10.4" TFT LCD, LED Backlight 1000 nits, XGA
Display Area (mm)	211.2 (H) x 158.4(V) mm
Brightness	1000 cd/m ²
Resolution	1024 x 768 (XGA)
Contrast Ratio	600 : 1
Pixel Pitch (mm)	0.20625(H) x 0.20625(V)
Viewing Angle	140°(H), 120°(V)
Display Colors	262K
Response Time (Typical)	25ms (Typical)
Sync	LVDS
Power Consumption	15W
Dimensions (mm)	279(W) x 204(H) x 45(D)mm
Weight (Net)	1.3Kg
LED Driving Board	LID10B
Control Board (Optional)	<input type="checkbox"/> AD6038GD
<input type="checkbox"/> AD6038GD	VGA+DVI
F / R Control Button	<input type="checkbox"/> 4 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

*Specifications are subject to change without notice. **All brands or product names are trademarks or registered trademarks of their respective companies.

SLD/SLO = Panel+ LED Driving Board + Control Board + Housing

