

SLO1768(WT)

17" Open Frame TFT LCD Display, LED Backlight, 1600nits, SXGA (1280x1024)

17" open frame TFT LCD panel, built-in 1600 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marine, transportation, gaming, studio display, gas pump. transportation, and outdoor industrial application.



KEY FEATURES

- Sunlight Readable
- LED Backlight
- SXGA(1280x1024) High Definition
- High Shock & Vibration Resistance
- Low Power Consumption
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Wide Operation temperature
- Life Expectancy
- Smart Panel design.

The thickness is only 36.2mm

SPECIFICATIONS

Model No.	SLO1768(WT)
Description	17" Open Frame TFT LCD Display, LED Backlight, 1600nits, SXGA(1280x1024)
Display Area (mm)	337.9(H) x 270.3 mm
Brightness	1600 cd/m ²
Resolution	1280x1024 (SXGA)
Contrast Ratio	1000 : 1
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Viewing Angle	+85°~-85°(H), +80°~-80°(V)
Display Colors	16.7M
Response Time (Typical)	30ms
Power Consumption	36.55W
Dimensions (mm)	389.7x297.3x36.2mm
Weight (Net)	2.5kg
LED Driving Board	LID17A09
Control Board (Optional)	<input type="checkbox"/> AD2662GDVAR
<input type="checkbox"/> AD2662GDVAR	VGA+DVI (Optional S-Video/ Component / Audio)
F / R Control Button	<input type="checkbox"/> 4 Key <input type="checkbox"/> 5 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
<input type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

*Specifications are subject to change without notice. **All brands or product names are trademarks or registered trademarks of their respective companies.

SLD/SLO = Panel+ LED Driving Board + Control Board + Housing

Note :
 O.D : Outline Dimension
 B.O : Bezel Opening
 A.A : LCD Active Area

