

SLO2137

21.5" Wide TFT LCD, LED Backlight 1400nits, FHD (1920x1080)

21.5" wide is a full high definition (FHD) LCD panel, built-in 1400 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marine, transportation, gaming, studio display, gas pump.



KEY FEATURES

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy

APPLICATIONS

- Marine
- Military
- Medical
- Transportation
- Industrial

SPECIFICATIONS

Model No.	SLO2137
Description	21.5" Wide TFT LCD, LED Backlight 1400 nits, FHD
Display Area (mm)	476 (H) x 267.7(V)
Brightness	1400 cd/m ²
Resolution	1920 x 1080 (FHD)
Contrast Ratio	1300 : 1
Pixel Pitch (mm)	0.08265(H) x 0.24795(V)
Viewing Angle	178°(H), 178°(V)
Display Colors	16.7M
Response Time (Typical)	5ms
Sync	LVDS
Power Consumption	50W
Dimensions (mm)	545(W) x 370(H) x 60(D)mm
Weight (Net)	5.5Kg
LED Driving Board	LID21A
Control Board (Optional)	<input type="checkbox"/> AD2662GD <input type="checkbox"/> AD2662GDVAR
<input type="checkbox"/> AD2662GD	VGA+DVI
<input type="checkbox"/> AD2662GDVAR	VGA+DVI (Optional S-Video/ Component / Audio)
F / R Control Button	<input type="checkbox"/> 4 Key <input type="checkbox"/> 5 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
<input type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

*Specifications are subject to change without notice. **All brands or product names are trademarks or registered trademarks of their respective companies.

SLD/SLO = Panel+ LED Driving Board + Control Board + Housing

