

# SLO2425

24" TFT LCD, Wide Viewing Angle, LED Backlight 1000nits, FHD (1920x1080)

The 24" TFT LCD panel boasts 1000 nits of high brightness for sunlight readability, a high transmittance color filter, polarizing plates, low power consumption, and so much more. It is suitable for kiosks, digital outdoor advertising, marine monitoring, transportation, gaming, studio and gas pump displays, and any outdoor application.



## KEY FEATURES

- Sunlight Readable
- LED Backlight
- FHD(1920x1080) High Definition
- High Shock & Vibration Resistance
- Low Power Consumption
- Wide Viewing Angle
- High Uniformity
- Low EMI Noise
- Wide Dimming
- LCD Blacking Defect Free (HTNi 110°C)


## SPECIFICATIONS

Model No.	SLO2425
Description	24" TFT LCD, LED Backlight 1000nits,FHD(1920x1080)
Display Area (mm)	531.36 x 298.89 mm
Brightness	1000 cd/m <sup>2</sup>
Resolution	1920 x 1080 (FHD)
Contrast Ratio	5000 : 1
Pixel Pitch (mm)	0.276(H) x 0.276(V)
Viewing Angle	+89°~-89°(H), +89°~-89°(V)
Display Colors	16.7M
Response Time (Typical)	25ms
Sync	LVDS
Power Consumption	38W
Dimensions (mm)	586.4(W)x325.6(H)x36.5(D)
Weight (Net)	4.2Kg
LED Driving Board	LID 24A
Control Board (Optional)	<input type="checkbox"/> AD2662GD <input type="checkbox"/> AD2662GDVAR
<input type="checkbox"/> AD2662GD	VGA+DVI
<input type="checkbox"/> AD2662GDVAR	VGA+DVI (Optional S-Video/ Component / Audio)
F / R Control Button	<input type="checkbox"/> 4 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen


\*Specifications are subject to change without notice. \*\*All brands or product names are trademarks or registered trademarks of their respective companies.

SLD/SLO = Panel+ LED Driving Board + Control Board + Housing

Front View




Rear View



MECHANICAL DRAWING Unit: mm

Bottom View



Real View

