

DLF/DLH1335-A V1

13.3" TFT LCD, LED Backlight 1000nits, 1920x1080

The DLF/DLH1335-A is a 13.3 inch industrial grade sunlight readable LCD, with a high brightness of 1000 nits and high color saturation. It produces sharp images, crisp text and lifelike colors. The Durapixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor, kiosk, factory automation, military, transportation and gaming applications.



KEY FEATURES

- High Brightness 1000 nits
- Sunlight Readable
- LED Backlight
- Low Power Consumption
- Wide Operation Temperature
- BL MTBF: 100,000 hours

SPECIFICATIONS

Model No.	DLF/DLH1335-A V1
Description	13.3" TFT LCD, LED Backlight 1000 nits, 1920x1080
Display Area (mm)	293.47(H) x 165.08(V)
Brightness	1000 cd/m ²
Resolution	1920x1080
Aspect Ratio	16 : 9
Contrast Ratio	800 : 1
Pixel Pitch (mm)	0.15285(H) x 0.15285(V)
Pixel Pre Inch (PPI)	166
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	90%
Display Colors	16.7M
Response Time (Typical)	25ms
Panel Interface	LVDS
AD Board Input Interface	<input type="checkbox"/> DVI-I, HDMI, DP
AD Board Input Power	DC12V
Power Consumption	TBD
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Dimensions (mm)	309.7 x 184.1 x 9.6
Bezel Size(U/B/L/R)	5.77/11.65/7.31/7.31 mm
Weight (Net)	0.8kg
Operating Temperature	-20 °C ~ 70 °C
Storage Temperature	-20 °C ~ 70 °C

*Specifications are subject to change without notice. **All brands or product names are trademarks or registered trademarks of their respective companies.

DLF= Panel + LED Driving Board

DLH= Panel + LED Driving Board + AD Control Board

MECHANICAL DRAWING Unit: mm

